

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095870 A1

(51) International Patent Classification⁷: **F24H 3/08**

(21) International Application Number:
PCT/US2004/006482

(22) International Filing Date: 3 March 2004 (03.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **BECKETT GAS, INC.** [US/US]; 38000 Taylor Parkway, North Ridgeville, OH 44039 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SLABY, Terrance, C.** [US/US]; 8370 Parkdale Drive, North Royalton, OH 44133 (US).

(74) Agent: **HLAVKA, John, R.**; Watts Hoffmann Co., L.P.A., P.O. Box 99839, Cleveland, OH 44199-0839 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,


AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FURNACE



(57) Abstract: A gas fired furnace capable of operating with a 16:1 turndown ratio or greater. The furnace includes a plurality of burners (10) grouped into at least (14a) first and second (14b) groups, each group connected to a source of combustible gas through a control valve (30a, 30b, 30c). The control valve (30c) controlling at least one group of burners is of a modulating type having an output proportional to a control signal applied to the valve. The burners fire into associated heat exchange tubes (20a), each tube having an inlet (24) and an outlet. The tube outlets are connected to a collector chamber (44) that includes a baffle plate (60) that divides the collector into two sections, one of the sections communicating with the outlets of the tubes associated with the first group of burners, the other section communicating with the outlets of the heat exchanger tubes associated with the other group of burners.

WO 2005/095870 A1